

1030/1053-1120nm High Power WDM Filter

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Value
Pass Channel Wavelength Range λ_1	nm	1030 $\pm$ 4
Reflective Channel Wavelength Range λ_2	nm	1053 $\pm$ 10, 1064 $\pm$ 10, 1070 $\pm$ 10 1080 $\pm$ 10, 1092 $\pm$ 5, 1120 $\pm$ 5
Insertion Loss	Pass Channel@ λ_1	dB
	Reflective Channel@ λ_2	dB
Configuration	Y Type	-
	X Type	-
Isolation	Pass Channel@ λ_2	dB
	Reflective Channel@ λ_1	dB
Optical Return Loss		dB
Directivity		dB
Polarization Dependent Loss		dB
Fiber Type	-	HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm
	Metal Box	mm

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFWM-	NN	NN	-	(C)	-	HP NN	-	(C)	(C)	C	NN	-	CC/CCC
Ref Wavelength	Pass Wavelength	Configuration	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type					
05= 1053nm	03= 1030nm	X=X Type	1=1W	M= Metal Box	E= 10/125 SC Fiber	B= Bare Fiber	05=0.5m	N= Without Connector					
06= 1064nm		Blank for Y Type	5=5W	Blank for SST	Q= 20/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector					
08=1080nm			10=10W	or >10W	R= 25/250 DC Fiber	2=2mm Cable	15=1.5m	LC/PC=LC/PC Connector					
12=1120nm			20=20W		Blank for HI1060 Fiber	3=3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector					